

Conference Calls made Simple and Effortless

KX-HDV800

The clear choice for better collaboration



KEY FEATURES

- High Quality Sound with Omnidirectional Mic.
- Designated Smartphone App
- Integration with UC Application
- Conference Recording to SD Card

The Panasonic Conference App is your capable meeting assistant. Managing meetings is much more personal and direct when you're holding the user interface in your hand. Intuitively call contacts straight from your local address book, create conference groups, adjust the volume and more during meetings by using your mobile or tablet. You no longer need to get up and operate the keypad of the conference phone that is far away at the centre of the table.

[Tell me more about the KX-HDV800 >>](#)

SPECIFICATIONS

| | |
|-----------------------|---|
| USB | 1 port (USB 2.0, mini B) |
| LAN Port | Ethernet 10/100 Base T |
| DC Input | 1 port (for optional AC Adaptor) |
| LCD Display | Illuminated graphics, 128x64 |
| LCD Backlight | Yes |
| PoE | IEEE 802.3af, Class III |
| LED Indication | Flashing blue: Incoming call, Steady blue: Call in progress, Flashing red: On hold, microphone and speakers turned off, Steady red: Mute, microphone turned off |
| AC Adaptor | KX-A424 (Option) 100v - 240v AC / 12 V DC |
| Bluetooth | 1 ch (V4) |

| | |
|---------------------------------|---|
| Expansion microphone | KX-HDV801 (x 2 pcs) |
| RJ9 for expansion mic | 2 ports |
| AUX | 1 port (RJ9, for wireless headset) |
| NFC | NFC Forum Type 4 and ISO/IEC 14443 Type A |
| IPv6 | Yes |
| IPv4 | Yes |
| IP Addressing | DHCP, Static addressing |
| Security | TLS (TLS v1.0, TLS v1.1, TLS v1.2) |
| VLAN | Yes (802.1Q) |
| Syslog | No |
| QoS | DiffServ, VLAN |
| Codec | G722, G711 A-law, G711 μ -law, G729ab |
| VoIP Signaling Protocol | SIP 2.0 (RFC 3261 and companion RFCs) |
| Line | 4 lines |
| Speakerphone | Full duplex, Frequency band 200 Hz - 7000 Hz |
| Conference | 5-way |
| Ringtones | 6 levels |
| Wideband Audio | Yes |
| Key | Dial keys (0-9, *, #), Menu, Navigation, No/End/Back/Start/Stop recording, OK, Volume, Mute, Hold, Answer, Hang up/end call, Conference, Line selection |
| Microphone | Omnidirectional, 360 degrees |
| Weight | 1 kg |
| Operating Temperature | 0 °C - 40 °C |
| Power Consumption | POE/Ac Adapter 3.2W (Standby) / 5.5W (Talking) |
| Operating Humidity | 20% - 80% condensation free |
| Memory | Support for SD and SDHC (Recording 35 hr / Gb) |
| Frequency Band | Bluetooth - 2.402 Ghz to 2.480 Ghz |
| Phone Book (Entries) | 1000 entries per profile (4 password protect profiles) |
| Dimension (W x D x H mm) | 275 x 240 x 77 |
| Daylight Saving Time | Configurable for automatic adjustments |
| DTMF | RFC2833, SIP INFO, In-band |
| NAT Traversal | STUN, ICE and TURN |
| Configuration area | Via integrated web server, HTTP or HTTPS. Separate user and administrator login |
| Anti-theft protection | Kensington security slot |
| Transport | UDP, TCP, TLS and SIPS |
| Time Servers | NTP and SNTP |
| Device Management | Support for easy configuration and updating of multiple conference phones |
| External | Support for LDAP |
| Equalizer | Soft, Neutral, Bright |
| Colour | Liquorice Black |

URL: <https://business.panasonic.cz/komunikacni-reseni/kx-hdv800>

CONTACT

Web: <https://business.panasonic.cz/komunikacni-reseni/contact-us>

